



CAVALLO s.r.l.
via Mulino 5/B
20090 BUCCINASCO (Milano) ITALY
T.++39.0245101515 Fax +39.0245100234
e-mail: info@cavallocom.it www.cavallocom.it



700SC Refrigerated Cabinet without electrical contacts



Refrigerated air ventilated Cabinet without electrical contacts inside the chamber, ideal for use with materials releasing vapors. Air Extraction system by centrifugal fan, may be connected to external aspiration. Timer for air exchange inside the chamber. Anti-dust filter inlet.

Temperature range: -2°C /+8°C

Structure made entirely of stainless steel as per AISI 304 with Scotch-brite exterior finish. Rounded inner corners for easy cleaning operations, bottom bowl to contain spills.

Single Door with rubber gasket, magnetic type. Self-closing system for openings <90°. Full-grip handle entirely made from the door structure, for easy opening and immediate cleaning. Lock and key.

The insulation thickness is 60 mm polyurethane injected CFC and HCFC.

Internal lighting: lamp activated when door open.

Traditional Refrigeration unit: continuous forced ventilation, located at the top of the structure. The ventilated refrigeration system allows a good distribution of set temperature inside the chamber.

The evaporator provides maximum surface of thermic exchange. Condense evaporation through electrical device. CFC-free R404 refrigerant.

Compressor Cooling power: 407W at +35°C ambient temperature, evaporation -10°C and condensation: +55°C.

Tropicalized compressor (+43°C).

Defrosting: automatic hot gas

Double temperature probe.

Control panel: Touch screen front panel. Keypad lock function. Door open alarm. Possibility to select temperatures in °C or °F. Fast overcooling function.

n.3 Plastic-coated racks with adjustable rails.

n.4 Adjustable stainless steel **Feet** 55 mm. These adapt the cabinet to any situation by adjusting height and angle.

Electricity (V/ph/Hz): 230 / 1 / 50 - Watt 393 – CE marking

Capacity: 700 ltrs

External dimensions (LxPxH mm): 700x810x2060 **net weight (Kg):** 104

Overall dimensions (LxPxH mm): 750x890x2200 **gross weight (Kg):** 112

Optional: cable entry hole/port, Castors Kit

Made in Italy